
## DURAN® Burette Amber, with Schellbach stripe and PTFE key, class AS


with straight standard ground stopcock, white inscription, waiting time: 30 seconds, with batch certificate and certificate of conformity

With Schellbach stripe and main graduations as circular divisions. Calibration is based on the poured out volume ("Ex") at a +20 °C reference temperature. Volume content tolerances conform to DIN.

Typical application: titrations.

| Cat. No. | Capacity (mL) | l (mm) | Accuracy limits (mL) | Graduation (mL) | Pack Unit |
|---|---|---|---|---|---|
| 243362708 | 10 | 820 | 0.02 | 0.02 | 2 |
| 243363301 | 25 | 820 | 0.03 | 0.05 | 2 |
| 243363601 | 50 | 820 | 0.05 | 0.1 | 2 |
| 243363901 | 100 | 870 | 0.1 | 0.2 | 2 |



ISO 385 | A 121 °C


## DURAN® Burette, class B

with straight standard ground stopcock

Calibration is based on the poured out volume ("Ex") at a +20 °C reference temperature. Volume content tolerances conform to DIN and ISO. The Class B accuracy limit is roughly one and a half times wider than for Class AS. The tolerances are thus more strict than specified by DIN.

Typical application: titrations.

| Cat. No. | Capacity (mL) | h (mm) | Accuracy limits (mL) | Graduation (mL) | Remark | Pack Unit |
|---|---|---|---|---|---|---|
| 243282703 | 10 | 820 | 0.03 | 0.02 | | 2 |
| 243283305 | 25 | 820 | 0,04 | 0.05 | | 2 |
| 243283605 | 50 | 820 | 0,08 | 0.1 | | 2 |
| 243283905 | 100 | 870 | 0,15 | 0.2 | Non-DIN/ ISO size. | 2 |






ISO 385 | A 121 °C